

# BO 45 surface

049-623041XV 002-90726



Project / Type


Notes

Count / Date



Cylindrical spotlight in aluminium; surface special colours powder coated; 350° rotatable and 90° tiltable; with surface mounted housing; passive cooling of the LEDs through improved heat sink geometry; with high power LED for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 8° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC2; 220-240 V; incl. converter, non dimmable; external converter for ceiling insertion, through-wiring suitable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



super spot 8°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 14200    | 0.14  |
| 2     | 3500     | 0.28  |
| 3     | 1600     | 0.41  |
| 4     | 900      | 0.55  |
| 5     | 600      | 0.69  |

## Product drawing



## General

Ceiling | Track

tilt max 90°

rotation 350°

special colours

IP20

406 lm

fixture 59 lm/W <sup>1</sup>

## LED

2700 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 | R<sub>r</sub>: 91 | R<sub>t(15)</sub>: 89

MR 0.54 | MDER 0.49

## Optical

super spot | beam angle 8°

PstLM ≤ 1.0 <sup>2</sup> | SVM ≤ 0.4 <sup>2</sup>

## Electrical

non DIM

PC2 | 220-240 V

system 9.2 W | fixture 6.9 W

11 Vf | 600 mA

## Physical

diameter 45 mm | height 155 mm

0.4 kg

<sup>1</sup> incl. consideration of optical losses & internal control unit losses  
<sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator



# BO 45 surface

049-623041XV 002-90726



Project / Type

Notes

Count / Date

## Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|--------|--------|--------|--------|--------|
| LLMF               | 0.97   | 0.94   | 0.91   | 0.88   | 0.85   |
| LSF                | 1      | 1      | 1      | 1      | 1      |

MF

LMF × RSMF × LLMF × LSF

MF

Maintenance Factor

LMF<sup>a</sup>

Luminaire Maintenance Factor

RSMF<sup>a</sup>

Room Surface Maintenance Factor

LLMF

Lamp Lumens Maintenance Factor

LSF

Lamp Survival Factor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Components

### POWER SUPPLY


|            |                   |
|------------|-------------------|
| L-W-H (MM) | ARTICLE NUMBER(S) |
| 210-30-21  | 002-90726         |



## Optional electrical accessories

### DIN RAIL POWER SUPPLY

|            |                   |
|------------|-------------------|
| L-W-H (MM) | ARTICLE NUMBER(S) |
| 72-90-63   | 005-6520210       |



### DIN RAIL LED DRIVER

|                                |            |                   |
|--------------------------------|------------|-------------------|
| TYPE                           | L-W-H (MM) | ARTICLE NUMBER(S) |
| 2 × 42W   48V DC   UOUT 10–40V | 36-88-59   | 005-6121030       |



## Optical accessories

### HONEYCOMB LOUVER

|           |        |                   |
|-----------|--------|-------------------|
| COLOUR    | Ø (MM) | ARTICLE NUMBER(S) |
| jet black | 42     | 007-1965188       |



# BO 45 surface

049-623041XV 002-90726



Project / Type

Notes

Count / Date

## Optical accessories

### OVAL LENS

|        |                   |
|--------|-------------------|
| Ø (MM) | ARTICLE NUMBER(S) |
| 42     | 007-1965880       |



### SOFT LENS

|        |                   |
|--------|-------------------|
| Ø (MM) | ARTICLE NUMBER(S) |
| 42     | 007-1965980       |



### WALLWASHER LENS

|        |                   |
|--------|-------------------|
| Ø (MM) | ARTICLE NUMBER(S) |
| 42     | 007-1965780       |

