

TASK direct / indirect power

free standing double

X059-2962158Z



Project / Type	
Notes	
Count / Date	



General

Floor , Standing	
black , RAL9005 ¹	
IP20	
indirect 15600 lm	
direct 5110 lm	
total 20710 lm	

LED

4000 K	
CRI ≥ 90	
L90 / 50000 h	
photobio. safety RG 0 - no Risk	
initial MacAdam ≤ 3 SDCM	
R _g : 96 , R _r : 90 , R _{t(1-15)} : 87	
MR 0.75	
MDER 0.68	

Optical

Microprismatic	
UGR < 13 , ≥65° <3000 cd/m ²	
PstLM ≤ 1.0 ²	
SVM ≤ 0.4 ²	

Electrical

touch DIM on pole	
161 W	
PC1 220-240V	
129 lm/W	

Physical

U-shape	
length 800 mm	
width 940 mm	
height 2054 mm	
13.2 kg	


¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Free standing luminaire with two rectangular luminaire head made of aluminium and rounded edges; luminaire heads arranged parallel; ultra low-profile design (only 15 mm); rectangular downpipe; pedestal with recess for table base (U-shape); surface black powder coated; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; microprismatic PMMA cover; completely homogeneous illumination; UGR ≤ 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; including TOUCH DIM control for individual control of the brightness; incl. connection cable (3m) with safety plug; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing

