

# SASSO 60 round adjustable

ceiling

048-31106319W



Project / Type

Notes

Count / Date



**General**

Ceiling , Surface

tilt max 30°

rotation 360°

black , RAL9005/gold <sup>1</sup>

Inner colour gold

IP20

920 lm

**LED**

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 97 , R<sub>r</sub>: 90 , R<sub>t(1-5)</sub>: 89

MR 0.81

MDER 0.74

**Optical**

wide flood

beam angle 54°

≥65° <3000 cd/m²

Cylindrical surface mounted spotlight in die-cast aluminium; suitable for ceiling mounting; surface black (housing/light inset); 360° rotatable and 30° tiltable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 54° beam; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); converter integrated into spotlight head; luminaire for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

**Electrical**

DALI-2

10.4 W

PC1 220-240V

88 lm/W

1 DALI Addr.

**Physical**


diameter 72 mm

height 108 mm

0.5 kg

<sup>1</sup> RAL code

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

