

**SASSO 60** round  
adjustable  
ceiling  
048-31104317W



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



**General**

Ceiling , Surface \_\_\_\_\_

tilt max 30° \_\_\_\_\_

rotation 360° \_\_\_\_\_

black , RAL9005/white <sup>1</sup> \_\_\_\_\_

Inner colour white \_\_\_\_\_

IP20 \_\_\_\_\_

842 lm \_\_\_\_\_

**LED**

2700 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 2 SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_

MR 0.53 \_\_\_\_\_

MDER 0.48 \_\_\_\_\_

**Optical**

wide flood \_\_\_\_\_

beam angle 54° \_\_\_\_\_

≥65° <3000 cd/m² \_\_\_\_\_

**Electrical**

DALI-2 \_\_\_\_\_

10.4 W \_\_\_\_\_

PC1 220-240V \_\_\_\_\_

81 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

**Physical**


diameter 72 mm \_\_\_\_\_

height 108 mm \_\_\_\_\_

0.5 kg \_\_\_\_\_

<sup>1</sup> RAL code

**Light distribution**



**Product drawing**



**Installation instructions**



**Lighting calculator**

