

SASSO 60 round adjustable  
ceiling  
048-31104314W



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



<b>General</b>	
Ceiling , Surface	
tilt max 30°	
rotation 360°	
black , RAL9005/matt silver <sup>1</sup>	
Inner colour matt silver	
IP20	
855 lm	

<b>LED</b>	
2700 K	
CRI ≥ 90	
L80 / 50000 h	
initial MacAdam ≤ 2 SDCM	
R <sub>g</sub> : 99 , R <sub>r</sub> : 91 , R <sub>t(1-15)</sub> : 89	
MR 0.53	
MDER 0.48	

<b>Optical</b>	
wide flood	
beam angle 54°	
≥65° <3000 cd/m²	


Cylindrical surface mounted spotlight in die-cast aluminium; suitable for ceiling mounting; surface black (housing/light inset); 360° rotatable and 30° tiltable; luminaire housing can be attached to mounting plate without tools by interlock; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 54° beam; degree of protection IP20; PC1 220-240V; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); converter integrated into spotlight head; luminaire for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

<b>Electrical</b>	
DALI-2	
10.4 W	
PC1 220-240V	
82 lm/W	
1 DALI Addr.	


<b>Physical</b>	
diameter 72 mm	
height 108 mm	
0.5 kg	

<sup>1</sup> RAL code

Light distribution



Product drawing



Installation instructions



Lighting calculator

