


# SASSO 100 round adjustable

trim 2 lamps

048-2720517X 048-2798318 002-90779



Project / Type
Notes
Count / Date



↑ IP20 ↓ IP40	220-240V	360° rotation	X-PERT	X-PERT
------------------	----------	---------------	--------	--------

## General

Ceiling , Recessed
tilt max 30°
rotation 360°
white , RAL9016 <sup>1</sup>
Mounting set jet black
front IP40 , back IP20
3080 lm

## LED

3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 100 , R <sub>f</sub> : 91 , R <sub>f(1-5)</sub> : 88
MR 0.59
MDER 0.53

## Optical

super wide flood
beam angle 63°
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2
40 W
total insets 34 W
PC2 220-240V
77 lm/W
1 DALI Addr.

## Physical


trim
length 218 mm
width 118 mm
height 95 mm
0.51 kg

## Cutout


diameter 105 mm
length 205 mm
min. ceiling thickness 2 mm
max. ceiling thickness 25 mm
recessed depth 100 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

