

SASSO 60 round adjustable

trimless

048-2622411W 048-2696117 002-90762



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Recessed
 tilt max 30°
 rotation 360°
 black , RAL9005 ¹
 Mounting set traffic white
 front IP40 , back IP20
 932 lm

LED

2700 K
 CRI ≥ 90
 L80 / 50000 h
 initial MacAdam ≤ 2 SDCM
 R_g: 99 , R_r: 91 , R₍₁₋₁₅₎: 89
 MR 0.53
 MDER 0.48

Optical

wide flood
 beam angle 54°
 ≥65° <3000 cd/m²
 PstLM ≤ 1.0 ²
 SVM ≤ 0.4 ²

Electrical

DALI-2
 12.6 W
 PC2 220-240V
 74 lm/W
 1 DALI Addr.

Physical

trimless
 diameter 73 mm
 height 48 mm
 0.28 kg


Cutout

diameter 73 mm
 recessed depth 120 mm


¹ RAL code ² Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface black; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 12.5/15/25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 54° beam; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

