

# SASSO 60 round adjustable

trimless exposed concrete


048-2622412W 048-2695210 002-90762



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Recessed  
 tilt max 30°  
 rotation 360°  
 chrome  
 front IP40 , back IP20  
 1010 lm

## LED

2700 K  
 CRI ≥ 90  
 L80 / 50000 h  
 initial MacAdam ≤ 2 SDCM  
 R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89  
 MR 0.53  
 MDER 0.48

## Optical

wide flood  
 beam angle 54°  
 ≥65° <3000 cd/m<sup>2</sup>  
 P<sub>stLM</sub> ≤ 1.0<sup>1</sup>  
 SVM ≤ 0.4<sup>1</sup>

## Electrical

DALI-2  
 12.6 W  
 PC2 220-240V  
 80 lm/W  
 1 DALI Addr.

## Physical

trimless  
 length 230 mm  
 width 230 mm  
 height 162 mm


## Cutout

recessed depth 120 mm


<sup>1</sup> Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface chrome; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; concrete housings for exposed concrete ceilings; for trimless installation; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 54° beam; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

