

SASSO 60 round adjustable

trimless

048-2622412S 048-2696117 002-90771



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Recessed _____
 tilt max 30° _____
 rotation 360° _____
 chrome _____
 Mounting set traffic white _____
 front IP40 , back IP20 _____
 586 lm _____

LED

2700 K _____
 CRI ≥ 90 _____
 initial MacAdam ≤ 3 SDCM _____
 R_g: 99 , R_f: 91 , R₍₁₋₁₅₎: 89 _____
 MR 0.53 _____
 MDER 0.48 _____

Optical

spot _____
 beam angle 12° _____
 UGR < 16 _____
 P_{stLM} ≤ 1.0¹ _____
 SVM ≤ 0.4¹ _____

Electrical

non DIM _____
 13.1 W _____
 PC2 220-240V _____
 45 lm/W _____

Physical

trimless _____
 diameter 73 mm _____
 height 48 mm _____


Cutout

diameter 73 mm _____
 recessed depth 60 mm _____


¹ Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface chrome; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 12.5/15/25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 12° beam; UGR ≤ 16; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

