

# SASSO 60 round adjustable

trimless exposed concrete


048-2622412S 048-2695210 002-90771



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Recessed \_\_\_\_\_  
 tilt max 30° \_\_\_\_\_  
 rotation 360° \_\_\_\_\_  
 chrome \_\_\_\_\_  
 front IP40 , back IP20 \_\_\_\_\_  
 586 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_  
 CRI ≥ 90 \_\_\_\_\_  
 initial MacAdam ≤ 3 SDCM \_\_\_\_\_  
 R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_  
 MR 0.53 \_\_\_\_\_  
 MDER 0.48 \_\_\_\_\_

## Optical

spot \_\_\_\_\_  
 beam angle 12° \_\_\_\_\_  
 UGR < 16 \_\_\_\_\_  
 PstLM ≤ 1.0 <sup>1</sup> \_\_\_\_\_  
 SVM ≤ 0.4 <sup>1</sup> \_\_\_\_\_

## Electrical

non DIM \_\_\_\_\_  
 13.1 W \_\_\_\_\_  
 PC2 220-240V \_\_\_\_\_  
 45 lm/W \_\_\_\_\_

## Physical

trimless \_\_\_\_\_  
 length 230 mm \_\_\_\_\_  
 width 230 mm \_\_\_\_\_  
 height 162 mm \_\_\_\_\_


## Cutout

recessed depth 60 mm \_\_\_\_\_


<sup>1</sup> Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface chrome; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; concrete housings for exposed concrete ceilings; for trimless installation; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 12° beam; UGR ≤ 16; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

