

# SASSO 60 round downlight

trim 2 lamps

048-2602512M 048-2698317 002-90762



Project / Type

Notes

Count / Date



↑ IP20

↓ IP44

220-240V

↺

↻

X-PERT

X-PERT

General

Ceiling , Recessed

rotation 360°

chrome

Mounting set traffic white

front IP44 , back IP20

2060 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f[1-5]</sub>: 88

MR 0.59

MDER 0.53

Optical

medium

beam angle 22°

UGR < 19

PstLM ≤ 1.0 <sup>1</sup>

SVM ≤ 0.4 <sup>1</sup>

Electrical

DALI-2

25.2 W

total insets 21.4 W

PC2 220-240V

82 lm/W

1 DALI Addr.

Physical

trim

length 147 mm

width 80 mm

height 48 mm

Cutout

diameter 70 mm

length 136 mm


min. ceiling thickness 2 mm

max. ceiling thickness 25 mm


recessed depth 110 mm

<sup>1</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



Installation instructions

Lighting calculator

