

# SASSO 60 round downlight

trimless

048-2602414W 048-2696117 002-90771



Project / Type

Notes

Count / Date



## General

Ceiling , Recessed  
 rotation 360°  
 matt silver  
 Mounting set traffic white  
 front IP44 , back IP20  
 1010 lm

## LED

2700 K  
 CRI ≥ 90  
 L80 / 50000 h  
 initial MacAdam ≤ 2 SDCM  
 R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89  
 MR 0.53  
 MDER 0.48

## Optical

wide flood  
 beam angle 55°  
 ≥65° <1500 cd/m<sup>2</sup>  
 PstLM ≤ 1.0<sup>1</sup>  
 SVM ≤ 0.4<sup>1</sup>

## Electrical

non DIM  
 12.6 W  
 PC2 220-240V  
 80 lm/W

## Physical

trimless  
 diameter 73 mm  
 height 48 mm  
 0.22 kg


## Cutout

diameter 73 mm  
 recessed depth 60 mm


<sup>1</sup> Value of containing product at full load (undimmed)

Round recessed spotlight in die-cast aluminium; 1 lamp; surface matt silver; installation without tools in mounting set due to patented ball catch system; round installation housing; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 12.5/15/25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 55° beam; degree of protection from below IP44 (from above IP20); PC2 220-240V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

