MOVE IT 25 / 45 ACOUSTIC square grid

inlay 050-231121W



Project / Type

Notes Count / Date

General

Luminaire / Track Mounted	
white	
fire resistance class: B-s1, d0	

Physical

panel only for NODE connector + track 1210 mm length 1235 mm | width 1235 mm | height 25 mm 4.2 kg

Acoustics

Alpha w (α_w) up to 1¹ SAC (sound absorption class) up to A¹ NRC up to 1.3¹ SAA up to 1.32¹

¹ Acoustic data calculations based on MOVE IT 25/45 acoustic square grid inlay, cavity 40cm

Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; square design; high quality visual and tactile surface with embossed pattern, white; foreign fiber inclusions possible; absorption of direct sound and sound reflected from the ceiling; this creates high acoustic performance; for installation in the MOVE IT 25 / 45 suspended system composed of node connectors and profiles; subsequent insertion in already installed MOVE IT suspended system possible; installation without tools;

Product drawing



['050-231121W'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply. @ XAL GmbH \cdot Auer-Welsbach-Gasse 36 \cdot 8055 Graz \cdot Austria \cdot www.xal.com







