

SETA 60 CONEX

reflector direct / indirect

socket / socket

suspended system
058-4139638R



Project / Type

Notes

Count / Date



Luminaire housing made of extruded aluminium profile; extremely slim design (only Ø 60 mm) linear; converter integrated into luminaire housing; for lighting systems; surface black powder coated; for suspended mounting (1500 mm cable suspension - oblique or straight - as an accessory); with integrated toolless suspension height adjustment on the luminaire; canopy for through wiring (available as an accessory); electrical connection of the luminaires via plug/socket system; connectors (L-, T- or X-shape) available as an accessory; luminaire connection rotatable around its own axis, which means that any spatial angle can be realized; extruded profile for improved thermal management; high gloss reflector with faceted design; direct/indirect illumination characteristic; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination, separately controllable; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



General

Ceiling | Suspended

black | RAL 9005 ¹

chrome

IP20

indirect 9270 lm | direct 9030 lm

total 18300 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.72 | MDER 0.65

Optical

Reflector | symmetric

UGR ≤ 16 | ≥65° <1500 cd/m²

PstLM ≤ 1.0 ² | SVM ≤ 0.4 ²

Electrical

DALI-2 | 2 DALI Addr.

PC1 | 220-240 V

system 110 W

system 166 lm/W ³


socket / socket

Physical

length 2936 mm | width 60 mm | height 60 mm

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Light distribution



Product drawing



Installation instructions



Lighting calculator



SETA 60 CONEX

reflector direct / indirect

socket / socket

suspended system

058-4139638R



Project / Type

Notes

Count / Date

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF | 0.98 | 0.96 | 0.94 | 0.92 | 0.9 |
| LSF | 1 | 1 | 1 | 1 | 1 |
| MF | LMF × RSMF × LLMF × LSF | | RSMF ^a | Room Surface Maintenance Factor | |
| MF | Maintenance Factor | | LLMF | Lamp Lumens Maintenance Factor | |
| LMF ^a | Luminaire Maintenance Factor | | LSF | Lamp Survival Factor | |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10 | 5 |
| B13 | 7 |
| B16 | 9 |
| B20 | 11 |
| C10 | 9 |
| C13 | 12 |
| C16 | 15 |
| C20 | 19 |

Mounting accessories

LINEAR CONNECTOR surface

| TYPE | COLOUR | Ø (MM) | ARTICLE NUMBER(S) |
|-------------------------|------------|--------|-------------------|
| mechanical | pure white | 60 | 058-3013117 |
| mechanical | jet black | 60 | 058-3013118 |
| mechanical & electrical | pure white | 60 | 058-3013127 |
| mechanical & electrical | jet black | 60 | 058-3013128 |



LINEAR CONNECTOR suspended

| TYPE | COLOUR | Ø (MM) | ARTICLE NUMBER(S) |
|-------------------------|------------|--------|-------------------|
| mechanical | pure white | 60 | 058-3013217 |
| mechanical | jet black | 60 | 058-3013218 |
| mechanical & electrical | pure white | 60 | 058-3013227 |
| mechanical & electrical | jet black | 60 | 058-3013228 |



L CONEX CONNECTOR

| TYPE | COLOUR | ARTICLE NUMBER(S) |
|-------------------------|------------|-------------------|
| mechanical & electrical | pure white | 058-3018727 |
| mechanical & electrical | jet black | 058-3018728 |



T CONEX CONNECTOR

| TYPE | COLOUR | ARTICLE NUMBER(S) |
|-------------------------|------------|-------------------|
| mechanical & electrical | pure white | 058-3018827 |
| mechanical & electrical | jet black | 058-3018828 |



X CONEX CONNECTOR

| TYPE | COLOUR | ARTICLE NUMBER(S) |
|-------------------------|------------|-------------------|
| mechanical & electrical | pure white | 058-3018927 |
| mechanical & electrical | jet black | 058-3018928 |



CONEX FLEX CONNECTOR

| TYPE | COLOUR | Ø (MM) | ARTICLE NUMBER(S) |
|-------------------------|------------|--------|-------------------|
| mechanical & electrical | pure white | 60 | 058-3018627 |
| mechanical & electrical | jet black | 60 | 058-3018628 |



[058-4139638R] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

18.06.2025

SETA 60 CONEX

reflector direct / indirect

socket / socket

suspended system

058-4139638R



Project / Type

Notes

Count / Date

Mounting accessories

CEILING MOUNTING SET

| COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|------------|------------|-------------------|
| pure white | 75-20-10 | 058-3014117 |
| jet black | 75-20-10 | 058-3014118 |



CABLE SUSPENSION

| TYPE | COLOUR | ARTICLE NUMBER(S) |
|-----------------------------------|--------|-------------------|
| cable suspension | chrome | 058-3014210 |
| cable suspension | black | 058-3014218 |
| cable suspension angular max. 60° | chrome | 058-3014310 |
| cable suspension angular max. 60° | black | 058-3014318 |



CONNECTOR CABLE SUSPENSION

| COLOUR | ARTICLE NUMBER(S) |
|--------|-------------------|
| chrome | 058-3018110 |
| black | 058-3018118 |



CANOPY

| COLOUR | Ø (MM) | ARTICLE NUMBER(S) |
|------------|--------|-------------------|
| pure white | 90 | 005-2600037 |
| jet black | 90 | 005-2600038 |



Electrical accessories

POWER FEEDER surface

| TYPE | COLOUR | ARTICLE NUMBER(S) |
|----------------------|------------|-------------------|
| end cap power feeder | pure white | 058-3010217 |
| end cap power feeder | jet black | 058-3010218 |
| middle power feeder | pure white | 058-3011217 |
| middle power feeder | jet black | 058-3011218 |



POWER FEEDER suspended

| TYPE | COLOUR | ARTICLE NUMBER(S) |
|----------------------|------------|-------------------|
| end cap power feeder | pure white | 058-3010417 |
| end cap power feeder | jet black | 058-3010418 |
| middle power feeder | pure white | 058-3011317 |
| middle power feeder | jet black | 058-3011318 |
| L CONEX power feeder | pure white | 058-3018737 |
| L CONEX power feeder | jet black | 058-3018738 |



Electrical accessories

ESSENTIAL SENSOR

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|-----------------------|------------|------------|-------------------|
| brightness & presence | pure white | 90-60-65 | 058-3019117 |
| brightness & presence | jet black | 90-60-65 | 058-3019118 |



SENSE SENSOR

| TYPE | COLOUR | ARTICLE NUMBER(S) |
|--|------------|-------------------|
| brightness, presence, temperature, sound pressure, humidity, CO2 | pure white | 058-3019217 |
| brightness, presence, temperature, sound pressure, humidity, CO2 | jet black | 058-3019218 |



["058-4139638R"] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

18.06.2025

SETA 60 CONEX

reflector direct / indirect

socket / socket

suspended system
058-4139638R



Project / Type

Notes

Count / Date

Optical accessories

END CAP

| COLOUR | ARTICLE NUMBER(S) |
|------------|-------------------|
| pure white | 058-3010017 |
| jet black | 058-3010018 |

Optical accessories

BLIND CHANNEL standard

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|------------------------------------|------------|------------|-------------------|
| plug/socket incl. through wiring | pure white | 585-60-60 | 058-4922037 |
| plug/socket incl. through wiring | jet black | 585-60-60 | 058-4922038 |
| plug/socket incl. through wiring | pure white | 1185-60-60 | 058-4924037 |
| plug/socket incl. through wiring | jet black | 1185-60-60 | 058-4924038 |
| plug/socket incl. through wiring | pure white | 2351-60-60 | 058-4928037 |
| plug/socket incl. through wiring | jet black | 2351-60-60 | 058-4928038 |
| plug/socket incl. through wiring | pure white | 2936-60-60 | 058-4929037 |
| plug/socket incl. through wiring | jet black | 2936-60-60 | 058-4929038 |

BLIND CHANNEL CONEX L/T/X

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|--------------------------------------|------------|------------|-------------------|
| socket/socket incl. through wiring | pure white | 585-60-60 | 058-4932037 |
| socket/socket incl. through wiring | jet black | 585-60-60 | 058-4932038 |
| socket/socket incl. through wiring | pure white | 1185-60-60 | 058-4934037 |
| socket/socket incl. through wiring | jet black | 1185-60-60 | 058-4934038 |
| socket/socket incl. through wiring | pure white | 2351-60-60 | 058-4938037 |
| socket/socket incl. through wiring | jet black | 2351-60-60 | 058-4938038 |
| socket/socket incl. through wiring | pure white | 2936-60-60 | 058-4939037 |
| socket/socket incl. through wiring | jet black | 2936-60-60 | 058-4939038 |

