

SETA 60 CONEX reflector

direct / indirect socket / socket

suspended system
058-4139537B



Project / Type

Notes

Count / Date



General
Ceiling , Suspended
white , RAL 9010 ¹
dark chrome
IP20
indirect 8140 lm
direct 5680 lm
total 13820 lm

LED
3000 K
CRI ≥ 80
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
MR 0.56
MDER 0.51


Optical
Reflector
symmetric
UGR ≤ 13 , ≥65° <1500 cd/m ²
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Luminaire housing made of extruded aluminium profile; extremely slim design (only Ø 60 mm) linear; converter integrated into luminaire housing; for lighting systems; surface white powder coated; for suspended mounting (1500 mm cable suspension - oblique or straight - as an accessory); with integrated toolless suspension height adjustment on the luminaire; canopy for through wiring (available as an accessory); electrical connection of the luminaires via plug/socket system; connectors (L-, T- or X-shape) available as an accessory; luminaire connection rotatable around its own axis, which means that any spatial angle can be realized; extruded profile for improved thermal management; high gloss reflector with faceted design; direct/indirect illumination characteristic; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination, separately controllable; UGR ≤ 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Electrical
DALI-2
220-240 V
system 110 W
system 126 lm/W ³
PC1
2 DALI Addr.

Physical
length 2936 mm
width 60 mm
height 60 mm

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator



SETA 60 CONEX reflector

direct / indirect socket / socket

suspended system

058-4139537B



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.94	0.92	0.9
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Factor	

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	5
B13	7
B16	9
B20	11
C10	9
C13	12
C16	15
C20	19

Mounting accessories

LINEAR CONNECTOR

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
mechanical incl. opal cover connector	pure white		058-3013117
mechanical incl. opal cover connector	jet black		058-3013118
mechanical & electrical incl. opal cover connector	pure white		058-3013127
mechanical & electrical incl. opal cover connector	jet black		058-3013128
mechanical incl. opal cover connector	pure white	60-18-7	058-3013217
mechanical incl. opal cover connector	jet black	60-18-7	058-3013218
mechanical & electrical incl. opal cover connector	pure white	37-23-10	058-3013227
mechanical & electrical incl. opal cover connector	jet black	37-23-10	058-3013228

L CONEX CONNECTOR

TYPE	COLOUR	ARTICLE NUMBER(S)
mechanical & electrical	pure white	058-3018727
mechanical & electrical	jet black	058-3018728



T CONEX CONNECTOR

TYPE	COLOUR	ARTICLE NUMBER(S)
mechanical & electrical	pure white	058-3018827
mechanical & electrical	jet black	058-3018828



X CONEX CONNECTOR

TYPE	COLOUR	ARTICLE NUMBER(S)
mechanical & electrical	pure white	058-3018927
mechanical & electrical	jet black	058-3018928



CONEX flex connector

COLOUR	ARTICLE NUMBER(S)
pure white	058-3018627
jet black	058-3018628



[058-4139537B] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

01.05.2025

SETA 60 CONEX reflector

direct / indirect socket / socket

suspended system

058-4139537B



Project / Type

Notes

Count / Date

Mounting accessories

MOUNTING SET

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
pure white	75-20-10	058-3014117
jet black	75-20-10	058-3014118



CABLE SUSPENSION

TYPE	COLOUR	ARTICLE NUMBER(S)
	chrome	058-3014210
	black	058-3014218
angular max. 60°	chrome	058-3014310
angular max. 60°	black	058-3014318



CONNECTOR CABLE SUSPENSION

COLOUR	ARTICLE NUMBER(S)
chrome	058-3018110
black	058-3018118



CANOPY

TYPE	COLOUR	Ø (MM)	ARTICLE NUMBER(S)
DALI-2	pure white	90	005-2600037
DALI-2	jet black	90	005-2600038



Electrical accessories

END CAP POWER FEEDER

TYPE	COLOUR	ARTICLE NUMBER(S)
	pure white	058-3010217
	jet black	058-3010218
5 × 1.5 mm ²	pure white	058-3010417
5 × 1.5 mm ²	jet black	058-3010418



MIDDLE POWER FEEDER

TYPE	COLOUR	ARTICLE NUMBER(S)
	pure white	058-3011217
	jet black	058-3011218
5 × 1.5 mm ²	pure white	058-3011317
5 × 1.5 mm ²	jet black	058-3011318



L CONEX POWER FEEDER

TYPE	COLOUR	ARTICLE NUMBER(S)
5 × 1.5 mm ²	pure white	058-3018737
5 × 1.5 mm ²	jet black	058-3018738



[058-4139537B] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

01.05.2025

SETA 60 CONEX reflector

direct / indirect socket / socket

suspended system

058-4139537B



Project / Type

Notes

Count / Date

Electrical accessories

ESSENTIAL SENSOR

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
brightness & presence	pure white	90-60-65	058-3019117
brightness & presence	jet black	90-60-65	058-3019118



SENSE SENSOR

TYPE	COLOUR	ARTICLE NUMBER(S)
brightness, presence, temperature, sound pressure, humidity, CO2	pure white	058-3019217
brightness, presence, temperature, sound pressure, humidity, CO2	jet black	058-3019218



Optical accessories

END CAP

COLOUR	ARTICLE NUMBER(S)
pure white	058-3010017
jet black	058-3010018



Optical accessories

BLIND CHANNEL standard

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
incl. through wiring	pure white	585-60-60	058-4922037
incl. through wiring	jet black	585-60-60	058-4922038
incl. through wiring	pure white	1185-60-60	058-4924037
incl. through wiring	jet black	1185-60-60	058-4924038
incl. through wiring	pure white	2351-60-60	058-4928037
incl. through wiring	jet black	2351-60-60	058-4928038
incl. through wiring	pure white	2936-60-60	058-4929037
incl. through wiring	jet black	2936-60-60	058-4929038



BLIND CHANNEL CONEX L/T/X

TYPE	COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
incl. through wiring	pure white	585-60-60	058-4932037
incl. through wiring	jet black	585-60-60	058-4932038
incl. through wiring	pure white	1185-60-60	058-4934037
incl. through wiring	jet black	1185-60-60	058-4934038
incl. through wiring	pure white	2351-60-60	058-4938037
incl. through wiring	jet black	2351-60-60	058-4938038
incl. through wiring	pure white	2936-60-60	058-4939037
incl. through wiring	jet black	2936-60-60	058-4939038

