

SETA 60 CONEX reflector

direct / indirect socket / socket

suspended system

058-4134538R



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

black , RAL 9005 ¹

chrome

IP20

indirect 3260 lm

direct 2650 lm

total 5910 lm

LED

3000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.56

MDER 0.51

Optical

Reflector

symmetric

UGR ≤ 16 , $\geq 65^\circ$ <1500 cd/m²

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

220-240 V

system 42 W

system 141 lm/W³

PC1

2 DALI Addr.

Physical

length 1181 mm

width 60 mm


height 60 mm

2.8 kg

¹ RAL code ² Value of containing product at full load (undimmed)

³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Light distribution



Product drawing



[058-4134538R] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

02.05.2025

Installation instructions



Lighting calculator

