

SASSO 40 round adjustable

trim 2 lamps

048-2820514S 048-2898318 002-90745



Project / Type


Notes

Count / Date




Round recessed spotlight in die-cast aluminium; 2 lamps; surface matt silver; 360° rotatable and 30° tilttable; , installation without tools in mounting set due to patented ball catch system; oval installation housing; with trim jet black; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 15° beam; UGR ≤ 16; degree of protection from below IP40 (from above IP20); PC2 220-240V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



↑ IP20
↓ IP40

220-240V

General

Ceiling , Recessed

tilt max 30°

rotation 360°

matt silver

jet black

front IP40 , back IP20

1010 lm

LED

3000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

Optical

spot

beam angle 15°

UGR < 16

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

DALI-2

17.5 W

total insets 14.9 W

PC2 220-240V

58 lm/W

Physical

trim

length 122 mm

width 60 mm

height 50 mm

0.1 kg

Cutout

diameter 56 mm

length 114 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 120 mm

¹ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

