

SASSO 40 round downlight

trim 2 lamps

048-2800514S 048-2898318 002-90744



Project / Type

Notes

Count / Date



↑ IP20

↓ IP44

220-240V

↺

General

Ceiling , Recessed

rotation 360°

matt silver

jet black

front IP44 , back IP20

902 lm

LED

3000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

Optical

spot

beam angle 17°

UGR < 13

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

non DIM

17.5 W

total insets 14.9 W

PC2 220-240V

52 lm/W

Physical

trim

length 122 mm

width 60 mm

height 50 mm

0.49 kg

Cutout

diameter 56 mm

length 114 mm


min. ceiling thickness 2 mm

max. ceiling thickness 25 mm


recessed depth 100 mm

Round recessed spotlight in die-cast aluminium; 2 lamps; surface matt silver; , installation without tools in mounting set due to patented ball catch system; oval installation housing; with trim jet black; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 17° beam; UGR ≤ 13; degree of protection from below IP44 (from above IP20); PC2 220-240V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

