

# NOBA 60 suspended

MOVE IT 10

030-6920638



Project / Type \_\_\_\_\_


Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



Decorative pendant light inset made of aluminium; surface jet black powder coated; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

## Light distribution



wide flood 67°

h (m)	EO° (lx)	ø (m)
1	908	1.31
2	227	2.63
3	101	3.94
4	57	5.26
5	36	6.57

## Product drawing



## General

Ceiling , Track Suspended \_\_\_\_\_

jet black , RAL9005 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

955 lm \_\_\_\_\_

## LED

4000 K \_\_\_\_\_

CRI  $\geq 90$  \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam  $\leq 2$  SDCM \_\_\_\_\_

R<sub>g</sub>: 97 , R<sub>f</sub>: 90 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.81 \_\_\_\_\_

MDER 0.74 \_\_\_\_\_

## Optical

Wide Flood \_\_\_\_\_

beam angle 67° \_\_\_\_\_

## Electrical

DALI-2 \_\_\_\_\_

8.1 W \_\_\_\_\_

PC3 \_\_\_\_\_

118 lm/W \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

## Physical

diameter 60 mm \_\_\_\_\_

height 60 mm \_\_\_\_\_

1500 mm \_\_\_\_\_

<sup>1</sup> RAL code

## Installation instructions



## Lighting calculator



[‘030-6920638’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com