

# NOBA 50 suspended

MOVE IT 10

030-6910637



Project / Type


Notes

Count / Date



Decorative pendant light inset made of aluminium; surface traffic white powder coated; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;


## Light distribution



wide flood 67°

h (m)	EO° (lx)	ø (m)
1	797	1.31
2	199	2.63
3	89	3.94
4	50	5.26
5	32	6.57

## Product drawing



## General

Ceiling , Track Suspended

traffic white , RAL9016 <sup>1</sup>

IP20

838 lm

## LED

4000 K

CRI  $\geq 90$

L80 / 50000 h

initial MacAdam  $\leq 2$  SDCM

R<sub>g</sub>: 97 , R<sub>f</sub>: 90 , R<sub>(1-15)</sub>: 89

MR 0.81

MDER 0.74

## Optical

Wide Flood

beam angle 67°

## Electrical

DALI-2

7.2 W

PC3

116 lm/W

1 DALI Addr.

## Physical

diameter 50 mm

height 50 mm

1500 mm

<sup>1</sup> RAL code

## Installation instructions



## Lighting calculator

