

TARO 45 downlight

MOVE IT 10 square
030-6710537M



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling / Wall , Track _____

traffic white , RAL 9016 ¹ _____

IP20 _____

983 lm _____

optical inset 99 lm/W² _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 100 , R_f: 91 , R_{f(1-15)}: 88 _____

MR 0.59 _____

MDER 0.53 _____

Optical

medium _____

beam angle 24° _____

PstLM ≤ 1.0 ³ _____

SVM ≤ 0.4 ³ _____

Electrical

DALI-2 _____

48 V _____

fixture 11.0 W _____

optical inset 9.9 W _____

PC3 _____

1 DALI Addr. _____


Physical

diameter 45 mm _____

height 75 mm _____


0.21 kg _____

Light distribution



medium 24°			
h (m)	E0° (lx)	ø (m)	
1	4730	0.43	
2	1180	0.86	
3	530	1.30	
4	300	1.73	
5	190	2.16	

Product drawing



¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Installation instructions

