

# TARO 45 downlight

MOVE IT 10 square  
030-6710534M



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



### General

Ceiling / Wall , Track \_\_\_\_\_

chrome \_\_\_\_\_

IP20 \_\_\_\_\_

983 lm \_\_\_\_\_

optical inset 99 lm/W<sup>1</sup> \_\_\_\_\_

### LED

3000 K \_\_\_\_\_

CRI ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam ≤ 2 SDCM \_\_\_\_\_

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 88 \_\_\_\_\_

MR 0.59 \_\_\_\_\_

MDER 0.53 \_\_\_\_\_

### Optical

medium \_\_\_\_\_

beam angle 24° \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

### Electrical

DALI-2 \_\_\_\_\_

48 V \_\_\_\_\_

fixture 11.0 W \_\_\_\_\_

optical inset 9.9 W \_\_\_\_\_

PC3 \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_


### Physical

diameter 45 mm \_\_\_\_\_

height 75 mm \_\_\_\_\_


0.12 kg \_\_\_\_\_

### Light distribution



| medium 24° |          |       |  |
|------------|----------|-------|--|
| h (m)      | E0° (lx) | ø (m) |  |
| 1          | 4730     | 0.43  |  |
| 2          | 1180     | 0.86  |  |
| 3          | 530      | 1.30  |  |
| 4          | 300      | 1.73  |  |
| 5          | 190      | 2.16  |  |

### Product drawing



<sup>1</sup> incl. consideration of optical losses  
<sup>2</sup> Value of containing product at full load (undimmed)

### Installation instructions

