

NOBA 40 adjustable

MOVE IT 10

030-6800638



Project / Type


Notes

Count / Date



Decorative spotlight inset made of aluminium; surface jet black powder coated; 365° rotatable and 90° tiltable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 67°; no multiple shadows; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;


Light distribution



wide flood 67°

h (m)	EO° (lx)	ø (m)
1	430	1.31
2	107	2.63
3	48	3.94
4	27	5.26
5	17	6.57

Product drawing



General

Ceiling / Wall , Track

tilt max 90°

rotation 365°

jet black , RAL9005 ¹

IP20

452 lm

LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 , R_f: 90 , R₍₁₋₁₅₎: 89

MR 0.81

MDER 0.74

Optical

Wide Flood

beam angle 67°

Electrical

DALI-2

3.5 W

PC3

129 lm/W

1 DALI Addr.

Physical

diameter 40 mm

height 40 mm

¹ RAL code

Installation instructions

