

NOBA 40 adjustable

MOVE IT 10

030-6800537



Project / Type _____


Notes _____

Count / Date _____



Decorative spotlight inset made of aluminium; surface traffic white powder coated; 365° rotatable and 90° tiltable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality plano-convex glass lens; beam angle 69°; no multiple shadows; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



wide flood 69°

h (m)	EO° (lx)	ø (m)
1	358	1.37
2	89	2.74
3	40	4.12
4	22	5.49
5	14	6.86

Product drawing



General

Ceiling / Wall | Track _____

tilt max 90° _____

rotation 365° _____

traffic white | RAL 9016 ¹ _____

IP20 _____

405 lm _____

optical inset 128 lm/W ² _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 100 | R_f: 91 | R_{f(1-15)}: 89 _____

MR 0.59 | MDER 0.53 _____

Optical

wide flood | beam angle 69° _____

PstLM ≤ 1.0 ³ | SVM ≤ 0.4 ³ _____

Electrical

DALI-2 | 1 DALI Addr. _____

PC3 | 48 V _____

fixture 3.5 W _____

optical inset 3.2 W _____

Physical

diameter 40 mm | height 40 mm _____

0.1 kg _____

¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Installation instructions

