

TARO 45 downlight

MOVE IT 10 square
030-6710434F



Project / Type

Notes

Count / Date



General

Ceiling / Wall | Track

chrome

IP20

1050 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 | R_f: 91 | R_{t(1-5)}: 87

MR 0.52 | MDER 0.47

Optical

flood | beam angle 36°

P_{stLM} ≤ 1.0^{1 2 3 4} | SVM ≤ 0.4^{1 2 3 4}

Electrical

DALI-2 | 1 DALI Addr.

PC3 | 48 V

fixture 10.9 W


fixture 96 lm/W⁵

Physical

diameter 45 mm | height 75 mm


Cylindrical spotlight in aluminium; surface polished chrome; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 36° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



| flood 36° | | |
|-----------|----------|-------|
| h (m) | E0° (lx) | ø (m) |
| 1 | 3130 | 0.65 |
| 2 | 780 | 1.29 |
| 3 | 350 | 1.94 |
| 4 | 200 | 2.59 |
| 5 | 130 | 3.23 |

Product drawing



Installation instructions

