

TARO 32 downlight

MOVE IT 10 square
030-6700637S



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling / Wall , Track _____

traffic white , RAL 9016 ¹ _____

IP20 _____

825 lm _____

optical inset 95 lm/W² _____

LED

4000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 97 , R_f: 90 , R₍₁₋₁₅₎: 89 _____

MR 0.81 _____

MDER 0.74 _____

Optical

spot _____

beam angle 18° _____

PstLM ≤ 1.0 ³ _____

SVM ≤ 0.4 ³ _____

Electrical

DALI-2 _____

48 V _____

fixture 9.6 W _____

optical inset 8.7 W _____

PC3 _____


1 DALI Addr. _____

Physical

diameter 32 mm _____


height 60 mm _____

Light distribution



spot 18°			
h (m)	E0° (lx)	ø (m)	
1	6250	0.32	
2	1560	0.63	
3	690	0.95	
4	390	1.27	
5	250	1.58	

Product drawing



¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Installation instructions

