

TARO 45 wallwasher/floor

MOVE IT 10 round
030-6790437W



Project / Type


Notes

Count / Date




Cylindrical spotlight in aluminium; surface traffic white powder coated; 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; with specially computed, asymmetrical reflector for homogeneous lighting intensity; no multiple shadows; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling / Wall , Track

rotation 360°

traffic white , RAL9016 ¹

IP20

733 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 97 , R_f: 91 , R_{f(1-15)}: 90

MR 0.53

MDER 0.48

Optical

WALLWASHER FLOOR

Electrical

DALI-2

11.0 W

PC3

67 lm/W

1 DALI Addr.

Physical

diameter 45 mm

height 75 mm

¹ RAL code

Installation instructions

