

MOVE IT 10 round
030-6790436W



Project / Type

Notes

Count / Date



Ceiling / Wall | Track

rotation 360°

brushed aluminium

IP20

780 lm

optical inset 112 lm/W¹

2700 K

CBI ≥ 90

1.85 / 500

```
initial MacAddress
```

Initial MacAulani ≤ 5 SDCM
 B = 404 / B = 22 / B = 22

R_g: 101 | R_f: 90 | R_{1-15}: 88

MR 0.51 | MDER 0.46

Optical

wallwasher floor

$$\text{PstLM} \leq 1.0^2 \mid \text{SVM} \leq 0.4^2$$

Electrical

DALI-2 | 1 DALI Addr.

PC3 | 48 V

fixture 9.3 W


optical inset 7.0 W

Physical


diameter 45 mm | height 75 mm

Cylindrical spotlight in aluminium; surface lacquered in brushed aluminium; 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; with specially computed, asymmetrical reflector for homogeneous lighting intensity; no multiple shadows; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional.

Light distribution



Product drawing



Installation instructions

¹ incl. consideration of optical losses² Value of containing product at full load (undimmed)