

MOVE IT 10 square
030-6780638W



Project / Type

Notes

Count / Date



Ceiling / Wall | Track

rotation 360° jet black | RAL 9005 ¹

IP20

845 lm

optical inset 121 lm/W²

4000 K

CRI ≥ 90

185 / 500

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_q: 99 | R_f: 92 | R_{1-15}: 90

MR 0.81 | MDER 0.74

wallwasher floor

$$\text{PstLM} \leq 1.0^3 \mid \text{SVM} \leq 0.4^3$$

DALI-2 | 1 DALI Addr.

PC3 | 48 V



fixture 9.3 W

optical inset 7.0 W

diameter 45 mm | height 75 mm

Cylindrical spotlight in aluminium; surface jet black powder coated; 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; with specially computed, asymmetrical reflector for homogeneous lighting intensity; no multiple shadows; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Product drawing



Installation instructions

