

# TARO 45 wallwasher/floor

MOVE IT 10 square  
030-6780637W




Project / Type	
Notes	
Count / Date	




Cylindrical spotlight in aluminium; surface traffic white powder coated; 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; with specially computed, asymmetrical reflector for homogeneous lighting intensity; no multiple shadows; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

## Light distribution



## Product drawing



## General

Ceiling / Wall , Track	
rotation 360°	
traffic white , RAL9016 <sup>1</sup>	
IP20	
791 lm	

## LED

4000 K	
CRI $\geq 90$	
L80 / 50000 h	
initial MacAdam $\leq 3$ SDCM	
R <sub>g</sub> : 94 , R <sub>r</sub> : 87 , R <sub>t(1-15)</sub> : 86	
MR 0.8	
MDER 0.72	

## Optical

WALLWASHER FLOOR	
------------------	--

## Electrical

DALI-2	
11.0 W	
PC3	
72 lm/W	
1 DALI Addr.	

## Physical

diameter 45 mm	
height 75 mm	

<sup>1</sup> RAL code

## Installation instructions

