

TARO 32 downlight

MOVE IT 10 square
030-6700538F



Project / Type _____

Notes _____

Count / Date _____



Cylindrical spotlight in aluminium; surface jet black powder coated; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 34° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;



General

Ceiling / Wall , Track _____

jet black , RAL9005 ¹ _____

IP20 _____

774 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 100 , R_f: 91 , R_{f(1-5)}: 88 _____

MR 0.59 _____

MDER 0.53 _____

Optical

Flood _____

beam angle 34° _____

Electrical

DALI-2 _____

9.6 W _____

PC3 _____

81 lm/W _____

1 DALI Addr. _____

Physical

diameter 32 mm _____


height 60 mm _____

Light distribution



| flood 34° | | | |
|-----------|----------|-------|--|
| h (m) | E0° (lx) | ø (m) | |
| 1 | 2520 | 0.61 | |
| 2 | 630 | 1.21 | |
| 3 | 280 | 1.82 | |
| 4 | 160 | 2.42 | |
| 5 | 100 | 3.03 | |

Product drawing



¹ RAL code

Installation instructions

