

MOVE IT 10 square
030-6780538W



Project / Type

Notes

Count / Date



Ceiling / Wall | Track

rotation 360° jet black | RAL 9005 ¹

IP20

813 lm

optical inset 117 lm/W²

3000 K

CRI $\geq .90$

1.85 / 500

initial MacAdams

Initial MacAdam ≤ 3 SDCM
P = 00 / P = 01 / P = 02

R_g: 99 | R_f: 91 | R_{1-15}: 89

MR 0.61 | MDER 0.55

wallwasher floor

$$\text{PstLM} \leq 1.0^3 \mid \text{SVM} \leq 0.4^3$$

DALI-2 | 1 DALI Addr.

PC3 | 48 V

fixture 9.3 W



optical inset 7.0 W

diameter 45 mm | height 75 mm

0.19 kg

Cylindrical spotlight in aluminium; surface jet black powder coated; 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; with specially computed, asymmetrical reflector for homogeneous lighting intensity; no multiple shadows; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Product drawing



Installation instructions

¹ RAL code ² incl. consideration of optical losses³ Value of containing product at full load (undimmed)