

MOVE IT 10 square  
030-6780537W



Project / Type

## Notes

Count / Date



Ceiling / Wall | Track

rotation 360°

traffic white | RAL 9016 <sup>1</sup>

IP20

831 lm

optical inset 119 lm/W<sup>2</sup>

## 3000 K

CRI  $\geq .90$

185 / 500

initial MacAdams

Initial MacAdam  $\leq 3$  SDCM  
P = 00 / P = 01 / P = 02

R<sub>g</sub>: 99 | R<sub>f</sub>: 91 | R<sub>{1-15}</sub>: 89

MR 0.61 | MDER 0.55

wallwasher floor

$$\text{PstLM} \leq 1.0^3 \mid \text{SVM} \leq 0.4^3$$

## DALI-2 | 1 DALI Addr.

PC3 | 48 V



fixture 9.3 W

optical inset 7.0 W

diameter 45 mm | height 75 mm

Cylindrical spotlight in aluminium; surface traffic white powder coated; 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; with specially computed, asymmetrical reflector for homogeneous lighting intensity; no multiple shadows; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

## Product drawing



## Installation instructions



# TARO 45 wallwasher/ floor

MOVE IT 10 square  
030-6780537W



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.982	0.954	0.926	0.899	0.873
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup>	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF	Lamp Survival Factor	

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Optical accessories

### HONEYCOMB LOUVER

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
jet black	42	007-1965188



## Optical accessories

### OVAL LENS

Ø (MM)	ARTICLE NUMBER(S)
42	007-1965880



### SOFT LENS

Ø (MM)	ARTICLE NUMBER(S)
42	007-1965980



### WALLWASHER LENS

Ø (MM)	ARTICLE NUMBER(S)
42	007-1965780

