

# TARO 32 downlight

MOVE IT 10 square  
030-6700537M



Project / Type

Notes

Count / Date



### General

Ceiling / Wall , Track

traffic white , RAL 9016 <sup>1</sup>

IP20

811 lm

optical inset 93 lm/W<sup>2</sup>

### LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 88

MR 0.59

MDER 0.53

### Optical

medium

beam angle 24°

PstLM ≤ 1.0 <sup>3</sup>

SVM ≤ 0.4 <sup>3</sup>

### Electrical

DALI-2

48 V

fixture 9.6 W

optical inset 8.7 W

PC3

1 DALI Addr.

### Physical

diameter 32 mm

height 60 mm

<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses

<sup>3</sup> Value of containing product at full load (undimmed)

### Light distribution



medium 24°

h (m)	EO° (lx)	ø (m)
1	4310	0.42
2	1080	0.83
3	480	1.25
4	270	1.67
5	170	2.09

### Product drawing



### Installation instructions

