

# TARO 45 downlight

MOVE IT 10 round  
030-6750436M



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



Cylindrical spotlight in aluminium; surface lacquered in brushed aluminium; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 24° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;



## General

Ceiling / Wall , Track \_\_\_\_\_

brushed aluminium \_\_\_\_\_

IP20 \_\_\_\_\_

926 lm \_\_\_\_\_

## LED

2700 K \_\_\_\_\_

CRI  $\geq 90$  \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam  $\leq 2$  SDCM \_\_\_\_\_

R<sub>g</sub>: 99 , R<sub>f</sub>: 91 , R<sub>{1-15}</sub>: 89 \_\_\_\_\_

MR 0.53 \_\_\_\_\_

MDER 0.48 \_\_\_\_\_

## Optical

Medium \_\_\_\_\_

beam angle 24° \_\_\_\_\_

## Electrical

DALI-2 \_\_\_\_\_

11.0 W \_\_\_\_\_

PC3 \_\_\_\_\_

84 lm/W \_\_\_\_\_


1 DALI Addr. \_\_\_\_\_

## Physical

diameter 45 mm \_\_\_\_\_


height 75 mm \_\_\_\_\_

## Light distribution



medium 24°		
h (m)	E0° (lx)	ø (m)
1	4460	0.43
2	1110	0.86
3	500	1.30
4	280	1.73
5	180	2.16

## Product drawing



## Installation instructions

