

TARO 32 downlight

MOVE IT 10 round
030-6740638S



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling / Wall | Track _____

jet black | RAL 9005 ¹ _____

IP20 _____

825 lm _____

LED

4000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 97 | R_f: 90 | R₍₁₋₁₅₎: 89 _____

MR 0.81 | MDER 0.74 _____

Optical

spot | beam angle 18° _____

P_{st}LM ≤ 1.0² ³ ⁴ ⁵ | SVM ≤ 0.4² ³ ⁴ ⁵ _____

Electrical

DALI-2 | 1 DALI Addr. _____

PC3 | 48 V _____

fixture 9.6 W _____


fixture 86 lm/W ⁶ _____

Physical

diameter 32 mm | height 60 mm _____


Cylindrical spotlight in aluminium; surface jet black powder coated; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 18° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



spot 18°			
h (m)	E ₀ ° (lx)	ø (m)	
1	6250	0.32	
2	1560	0.63	
3	690	0.95	
4	390	1.27	
5	250	1.58	

Product drawing



Installation instructions



TARO 32 downlight

MOVE IT 10 round
030-6740638S



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.89	0.85	0.82
LSF	1	1	1	1	1

MF

MF

LMF^a

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF^a

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Factor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Optical accessories

HONEYCOMB LOUVER

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
jet black	30	007-1965168



Optical accessories

OVAL LENS

Ø (MM)	ARTICLE NUMBER(S)
30	007-1965860



SOFT LENS

Ø (MM)	ARTICLE NUMBER(S)
30	007-1965960



WALLWASHER LENS

Ø (MM)	ARTICLE NUMBER(S)
30	007-1965760

