

# TARO 32 downlight

MOVE IT 10 round  
030-6740636S



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



Cylindrical spotlight in aluminium; surface lacquered in brushed aluminium; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 18° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;



### General

Ceiling / Wall , Track \_\_\_\_\_

brushed aluminium \_\_\_\_\_

IP20 \_\_\_\_\_

825 lm \_\_\_\_\_

### LED

4000 K \_\_\_\_\_

CRI  $\geq 90$  \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

initial MacAdam  $\leq 2$  SDCM \_\_\_\_\_

R<sub>g</sub>: 97 , R<sub>f</sub>: 90 , R<sub>(1-15)</sub>: 89 \_\_\_\_\_

MR 0.81 \_\_\_\_\_

MDER 0.74 \_\_\_\_\_

### Optical

Spot \_\_\_\_\_

beam angle 18° \_\_\_\_\_

### Electrical

DALI-2 \_\_\_\_\_

9.6 W \_\_\_\_\_

PC3 \_\_\_\_\_

86 lm/W \_\_\_\_\_


1 DALI Addr. \_\_\_\_\_

### Physical

diameter 32 mm \_\_\_\_\_


height 60 mm \_\_\_\_\_

### Light distribution



spot 18°			
h (m)	E0° (lx)	ø (m)	
1	6250	0.32	
2	1560	0.63	
3	690	0.95	
4	390	1.27	
5	250	1.58	

### Product drawing



### Installation instructions

