

TARO 32 downlight

MOVE IT 10 round
030-6740438S



Project / Type

Notes

Count / Date



Cylindrical spotlight in aluminium; surface jet black powder coated; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; precise radiation characteristic with 18° beam; no multiple shadows; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;



General

Ceiling / Wall , Track

jet black , RAL9005 ¹

IP20

734 lm

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_f: 91 , R_{1-15}: 89

MR 0.53

MDER 0.48

Optical

Spot

beam angle 18°

Electrical

DALI-2

9.6 W

PC3

76 lm/W


1 DALI Addr.

Physical

diameter 32 mm

height 60 mm


Light distribution



spot 18°

| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1 | 5560 | 0.32 |
| 2 | 1390 | 0.63 |
| 3 | 620 | 0.95 |
| 4 | 350 | 1.27 |
| 5 | 220 | 1.58 |

Product drawing



¹ RAL code

Installation instructions

