

TILA 22 suspended

MOVE IT 10

030-6630537F



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Track Suspended _____

traffic white , RAL 9016 ¹ _____

IP20 _____

354 lm _____

optical inset 69 lm/W² _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 100 , R_f: 91 , R_{f(1-15)}: 88 _____

MR 0.59 _____

MDER 0.53 _____

Optical

flood _____

beam angle 43° _____

PstLM ≤ 1.0 ³ _____

SVM ≤ 0.4 ³ _____

Electrical

DALI-2 _____

48 V _____

fixture 5.7 W _____

optical inset 5.1 W _____

PC3 _____

1 DALI Addr. _____

Physical


diameter 22 mm _____

height 100 mm _____

1500 mm _____


¹ RAL code ² incl. consideration of optical losses
³ Value of containing product at full load (undimmed)

Light distribution



flood 43°			
h (m)	E0° (lx)	ø (m)	
1	688	0.80	
2	172	1.59	
3	76	2.39	
4	43	3.19	
5	28	3.98	

Product drawing



Lighting calculator

