

TILA 32 adjustable

MOVE IT 10

030-6560434F



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling / Wall , Track _____

tilt max 135° _____

rotation 365° _____

chrome _____

IP20 _____

752 lm _____

optical inset 86 lm/W¹ _____

LED

2700 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89 _____

MR 0.53 _____

MDER 0.48 _____

Optical

flood _____

beam angle 34° _____

P_{stLM} ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

48 V _____

fixture 9.7 W _____

optical inset 8.7 W _____

PC3 _____

1 DALI Addr. _____

Physical


diameter 32 mm _____

height 120 mm _____

0.16 kg _____


¹ incl. consideration of optical losses
² Value of containing product at full load (undimmed)

Light distribution



flood 34°			
h (m)	E0° (lx)	ø (m)	
1	2450	0.61	
2	610	1.21	
3	270	1.82	
4	150	2.42	
5	100	3.03	

Product drawing



Installation instructions

