

# TILA 16 suspended

MOVE IT 10

030-6610536M



Project / Type	
Notes	
Count / Date	



### General

Ceiling , Track Suspended
brushed aluminium
IP20
187 lm
optical inset 71 lm/W <sup>1</sup>

### LED

3000 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 98 , R <sub>r</sub> : 91 , R <sub>(1-15)</sub> : 89
MR 0.6
MDER 0.55

### Optical

medium
beam angle 23°
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

### Electrical


DALI-2
48 V
fixture 3.3 W
optical inset 2.6 W
PC3
1 DALI Addr.

### Physical

diameter 16 mm
height 600 mm
0.27 kg
1500 mm

<sup>1</sup> incl. consideration of optical losses  
<sup>2</sup> Value of containing product at full load (undimmed)


### Light distribution



medium 23°

h (m)	E0° (lx)	ø (m)
1	894	0.41
2	223	0.81
3	99	1.22
4	56	1.62
5	36	2.03

### Product drawing



### Installation instructions



### Lighting calculator

