

# TILA 16 suspended

MOVE IT 10

030-6610534F



Project / Type

Notes

Count / Date




Decorative pendant light inset made of aluminium; surface polished chrome; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; high quality reflector; precise radiation characteristic with 31° beam; no multiple shadows; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

## Light distribution



flood 31°		
h (m)	E0° (lx)	ø (m)
1	588	0.56
2	147	1.12
3	65	1.67
4	37	2.23
5	24	2.79

## Product drawing



## General

Ceiling , Track Suspended

chrome

IP20

177 lm

## LED

3000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 98 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.6

MDER 0.55

## Optical

Flood

beam angle 31°

## Electrical

DALI-2

3.3 W

PC3

54 lm/W

1 DALI Addr.

## Physical

diameter 16 mm

height 600 mm

1500 mm

## Installation instructions



## Lighting calculator

