

TILA 16 suspended

MOVE IT 10

030-6600636M



Project / Type _____


Notes _____

Count / Date _____



Decorative pendant light inset made of aluminium; surface lacquered in brushed aluminium; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; pendant fitting with 1500mm suspension, incl. feed (black), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; high quality reflector; precise radiation characteristic with 23° beam; no multiple shadows; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;


Light distribution



medium 23°

h (m)	E0° (lx)	ø (m)
1	769	0.41
2	192	0.81
3	85	1.22
4	48	1.62
5	31	2.03

Product drawing



General

Ceiling , Track Suspended _____

brushed aluminium _____

IP20 _____

161 lm _____

LED

4000 K _____

CRI ≥ 90 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 94 , R_f: 87 , R₍₁₋₁₅₎: 90 _____

MR 0.86 _____

MDER 0.78 _____

Optical

Medium _____

beam angle 23° _____

Electrical

DALI-2 _____

3.3 W _____

PC3 _____

49 lm/W _____

1 DALI Addr. _____

Physical

diameter 16 mm _____

height 80 mm _____

1500 mm _____

Installation instructions



Lighting calculator



TILA 16 suspended

MOVE IT 10
030-6600636M



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.92	0.89	0.86
LSF	1	1	1	1	1

MF

MF

LMF^a

LMF × RSMF × LLMF × LSF

Maintenance Factor

Luminaire Maintenance Factor

RSMF^a

LLMF

LSF

Room Surface Maintenance Factor

Lamp Lumens Maintenance Factor

Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Mounting accessories

HOOK

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic white	16	030-1000017
jet black	16	030-1000018

