

# TILA 16 adjustable

MOVE IT 10  
030-6500637M



Project / Type


Notes

Count / Date



Decorative spotlight inset made of aluminium; surface traffic white powder coated; 365° rotatable and 135° tiltable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; high quality reflector; precise radiation characteristic with 23° beam; no multiple shadows; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

## Light distribution



medium 23°			
h (m)	E0° (lx)	ø (m)	
1	769	0.41	
2	192	0.81	
3	85	1.22	
4	48	1.62	
5	31	2.03	

## Product drawing



## General

Ceiling / Wall , Track

tilt max 135°

rotation 365°

traffic white , RAL9016 <sup>1</sup>

IP20

161 lm

## LED

4000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 94 , R<sub>f</sub>: 87 , R<sub>f(1-15)</sub>: 90

MR 0.86

MDER 0.78

## Optical

Medium

beam angle 23°

## Electrical

DALI-2

3.3 W

PC3

49 lm/W

1 DALI Addr.

## Physical

diameter 16 mm

height 80 mm

<sup>1</sup> RAL code

## Installation instructions

