

TILA 16 adjustable

MOVE IT 10
030-6500536M



Project / Type


Notes

Count / Date



Decorative spotlight inset made of aluminium; surface lacquered in brushed aluminium; 365° rotatable and 135° tiltable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; high quality reflector; precise radiation characteristic with 23° beam; no multiple shadows; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



medium 23°			
h (m)	E0° (lx)	ø (m)	
1	894	0.41	
2	223	0.81	
3	99	1.22	
4	56	1.62	
5	36	2.03	

Product drawing



General

Ceiling / Wall , Track

tilt max 135°

rotation 365°

brushed aluminium

IP20

187 lm

optical inset 71 lm/W¹

LED

3000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 98 , R_r: 91 , R_{t(1-15)}: 89

MR 0.6

MDER 0.55

Optical

medium

beam angle 23°

PstLM ≤ 1.0²

SVM ≤ 0.4²

Electrical

DALI-2

48 V

fixture 3.3 W

optical inset 2.6 W

PC3

1 DALI Addr.

Physical

diameter 16 mm

height 80 mm

0.05 kg

¹ incl. consideration of optical losses

² Value of containing product at full load (undimmed)

Installation instructions



TILA 16 adjustable

MOVE IT 10
 030-6500536M



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.92	0.89	0.86
LSF	1	1	1	1	1

MF
MF
LMF^a

LMF × RSMF × LLMF × LSF
 Maintenance Factor
 Luminaire Maintenance Factor

RSMF^a
LLMF
LSF

Room Surface Maintenance Factor
 Lamp Lumens Maintenance Factor
 Lamp Survival Factor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Mounting accessories

HOOK

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic white	16	030-1000017
jet black	16	030-1000018

