

GIRA wallwasher/floor

MOVE IT 10
030-6430637W



Project / Type

Notes

Count / Date



Linear light inset made of aluminium; surface traffic white powder coated; light inset 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; fitted with single LED light points; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; energy efficient LEDs with high CRI; good glare control through recessed light point level; with specially computed, asymmetrical reflector for homogeneous lighting intensity; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;



General

rotation 360°

traffic white , RAL9016 ¹

IP20

1480 lm

LED

4000 K

CRI ≥ 90

initial MacAdam ≤ 3 SDCM

R_g: 100 , R_f: 91 , R_{f(1-15)}: 88

MR 0.77

MDER 0.69

Optical

WALLWASHER FLOOR

Electrical

DALI-2

19.1 W

PC3

77 lm/W

1 DALI Addr.

Physical


length 217 mm

width 19 mm


height 19 mm

¹ RAL code

Light distribution



Product drawing



Installation instructions

