

GIRA wallwasher/floor

MOVE IT 10
030-6430637W



Project / Type

Notes

Count / Date



General

Ceiling , Track

rotation 360°

traffic white , RAL 9016 ¹

IP20

1480 lm

optical inset 87 lm/W²

LED

4000 K

CRI ≥ 90

L70 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 100 , R_f: 91 , R_{f(1-5)}: 88

MR 0.77

MDER 0.69

Optical

wallwasher floor

PstLM ≤ 1.0 ³

SVM ≤ 0.4 ³

Electrical

DALI-2

48 V

fixture 18.8 W

optical inset 16.9 W

PC3

1 DALI Addr.

Physical

length 217 mm

width 19 mm

height 19 mm


0.23 kg

¹ RAL code ² incl. consideration of optical losses


³ Value of containing product at full load (undimmed)

Linear light inset made of aluminium; surface traffic white powder coated; light inset 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; fitted with single LED light points; passive cooling of the LEDs through improved heat sink geometry; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 70% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; with specially computed, asymmetrical reflector for homogeneous lighting intensity; degree of protection IP20; PC3; 48 V; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;

Light distribution



Product drawing



Installation instructions



Lighting calculator

