

# TILA 32 adjustable

MOVE IT 10  
030-6560634M



Project / Type

Notes

Count / Date



### General

Ceiling / Wall , Track

tilt max 135°

rotation 365°

chrome

IP20

887 lm

### LED

4000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 97 , R<sub>f</sub>: 90 , R<sub>(1-15)</sub>: 89

MR 0.81

MDER 0.74

### Optical

Medium

beam angle 24°

### Electrical

DALI-2

9.7 W

PC3

91 lm/W


1 DALI Addr.

### Physical

diameter 32 mm

height 120 mm


### Light distribution



medium 24°

h (m)	E0° (lx)	ø (m)
1	4710	0.42
2	1180	0.83
3	520	1.25
4	290	1.67
5	190	2.09

### Product drawing



### Installation instructions



# TILA 32 adjustable

MOVE IT 10  
030-6560634M



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.96	0.92	0.88	0.85	0.81
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Mounting accessories

### HOOK

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic white	16	030-1000017
jet black	16	030-1000018



## Optical accessories

### HONEYCOMB LOUVER

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
jet black	30	007-1965168

