

GIRA wallwasher/floor

MOVE IT 10
030-6430538W



Project / Type

Notes

Count / Date



Linear light inset made of aluminium; surface jet black powder coated; light inset 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; fitted with single LED light points; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; energy efficient LEDs with high CRI; good glare control through recessed light point level; with specially computed, asymmetrical reflector for homogeneous lighting intensity; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;



General
rotation 360°
jet black , RAL9005 ¹
IP20
1370 lm


LED
3000 K
CRI ≥ 90
initial MacAdam ≤ 3 SDCM
R_g: 101, R_r: 91, R₍₁₋₁₅₎: 89
MR 0.59
MDER 0.53

Optical
WALLWASHER FLOOR


Electrical
DALI-2
19.1 W
PC3
72 lm/W
1 DALI Addr.

Physical
length 217 mm
width 19 mm
height 19 mm

Light distribution



Product drawing



¹ RAL code

Installation instructions

