

# GIRA wallwasher/floor

MOVE IT 10  
030-6430438W



Project / Type

Notes

Count / Date



Linear light inset made of aluminium; surface jet black powder coated; light inset 360° rotatable; light inset can be installed and moved without tools by means of clip mount; power supplied via MOVE IT system track profile; hot plug protection; fitted with single LED light points; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; energy efficient LEDs with high CRI; good glare control through recessed light point level; with specially computed, asymmetrical reflector for homogeneous lighting intensity; degree of protection IP20; PC3; DALI-2 control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional;



**General**  
rotation 360°  
jet black , RAL9005 <sup>1</sup>  
IP20  
1260 lm


**LED**  
2700 K  
CRI  $\geq 90$   
initial MacAdam  $\leq 3$  SDCM  
R<sub>g</sub>: 99 , R<sub>f</sub>: 93 , R<sub>f(1-15)</sub>: 91  
MR 0.53  
MDER 0.48

**Optical**  
WALLWASHER FLOOR


**Electrical**  
DALI-2  
19.1 W  
PC3  
66 lm/W  
1 DALI Addr.

**Physical**  
length 217 mm  
width 19 mm  
height 19 mm

## Light distribution



## Product drawing



<sup>1</sup> RAL code

## Installation instructions

